

Features

Model no. IOC100P


- Compact design
- CGA 870 compatible
- No batteries required
- Weighs less than one pound
- Single selector knob controls ON/OFF, liter flow and continuous flow mode
- Senses a breath and delivers an oxygen bolus in first third of the inspiratory cycle
- Delivers consistent volume of oxygen with each breath - up to 40 breaths per minute
- Limited two year warranty



Cylinder Duration Table

Setting		1	2	3	4	5	6	Continuous Flow			
Cylinder	Cylinder		Estimate	Estimated Cylinder Duration in Hours							
Туре	Volume (L)		Based or	Based on 20 BPM							
M2	36	1.9	0.9	0.6	0.5	0.4	0.3	0.3			
M4	113	5.9	2.9	2.0	1.5	1.2	1.0	0.9			
M6	164	8.5	4.3	2.8	2.1	1.7	1.4	1.4			
ML6	171	8.9	4.5	3.0	2.2	1.8	1.5	1.4			
M9	246	12.8	6.4	4.3	3.2	2.6	2.1	2.1			
_D	425	22.1	11.1	7.4	5.5	4.4	3.7	3.5			
Е	680	35.4	17.7	11.8	8.9	7.1	5.9	5.7			

Pulse Flow Waveforms¹



Setting 6

Technical Specifications

Weight	14.8 oz.								
Dimensions	5" L x 2.5" H x 2.5" W								
Pulse Dose Volumes	Setting	1	2	3	4	5	6		
	ml 02	28	43	64	78	91	103		
Continuous Flow	2 L/min +/- 0.5								
Required Operating Pressure	quired Operating Pressure 200 psi to 3000 psi								
Savings Ratio	3.5:1								
Cannula	Single lumen								
Regulator	built-in 25 +/- 5 psi								
Operating Temperature	32° F (0°C) to 122° F (50°C)								
Operating Altitude	0 to 10,000 feet								



Invacare Corporation

www.invacare.com

USA

One Invacare Way Elyria, Ohio 44035-4190 (800) 333-6900

Canada

570 Matheson Blvd. E. Unit 8 Mississauga, Ontario L4Z 4G4 Canada (800) 668-5324

© 2009 Invacare Corporation. All rights reserved. Trademarks are identified by the symbols TM and IM . All trademarks are owned by or licensed to Invacare Corporation unless otherwise noted. Specifications are subject to change without notification.

Form No. 09-010





Yes, you can:

