

INVACARE®
PLATINUM™ 10
OXYGEN CONCENTRATOR



The **Invacare® Platinum™ 10 Oxygen Concentrator** provides an attractive alternative to liquid systems and is known for reliability, performance and value. The 10 liter unit features quiet operation, a top handle and bottom recesses for easy handling and a side filter access door. In addition, the concentrator is compatible with the Invacare® HomeFill® Oxygen System and is available with an **Invacare® SensO₂® Oxygen Purity Sensor**.

Features

Pressure-based system is superior to timing-based systems

Self diagnostic electronics minimize troubleshooting time

Top handle for ease of mobility

Battery-free power loss alarm, Invacare® Sieve-GARD™ Monitor protects sieve from degradation, compressor 35 psi pressure-relief valve and low flow alarm

Provider Benefits

Provides continuous flow up to 10 liters per minute as an alternative to liquid systems

All Platinum 10 stationary concentrators include a HomeFill system port for inventory flexibility

Patient-accessible reset button helps minimize emergency service calls

Patient Benefits

User friendly design with easy to see control panel, humidifier bottle holder and filter access

HomeFill system compatibility allows patients with flow rates up to 5LPM to enjoy life's experiences with small, refillable cylinders

Reliable concentrator provides unlimited, worry-free oxygen supply

HCPCS Code: E1390



1. Invacare® HomeFill® Oxygen System connection
2. Easy to maintain filter
3. Also available with Invacare® SensO2® Oxygen Purity Sensor



Invacare Corporation
www.invacare.com

USA

One Invacare Way
Elyria, Ohio
44035-4190
(800) 333-6900

Canada

570 Matheson Blvd. E.,
Unit 8
Mississauga, Ontario
L4Z 4G4 Canada
(800) 668-5324

©2013

Invacare Corporation.
All rights reserved.
Trademarks are identified by the symbols ™ and ®. All trademarks are owned by or licensed to Invacare Corporation unless otherwise noted. Specifications are subject to change without notification.
Form No. 11-190
Rev. 04/13
130376



Model #	Dimensions	Weight	Shipping Weight	Quantity	Oxygen Flow	Flow Range	Maximum Outlet Pressure	Pressure Relief Mechanism
IRC10LX	26 3/8" H	54 lb.	60 lb.	1 Per Case	10 LPM	2-10 LPM	9+/- 0.5 PSI	35 PSI
IRC10LXO2	18 3/8" W 14 3/8" D			18 Per Pallet				+/- 3.5 PSI
	Oxygen Purity	Filter	Electrical Requirements	Rated Current Input	Average Power Consumption	Sound Level	Limited Warranty	
	94%-87% At All Flow Rates	Cabinet Compressor Inlet, +/- 10%, 60 Hz Outlet HEPA	120 VAC (132VAC/108VAC)	4.0 A	585 W	50 db. Average	3 Years	

All references to HCPCS codes: Providers are responsible for determining the appropriate billing codes when submitting claims to the Medicare program, and should consult an attorney or other advisor to discuss specific situations in further detail.