INVACARE® PERFECTO2™ V OXYGEN CONCENTRATOR





The Invacare® Perfecto2™ V Oxygen Concentrator is an economical addition to the premier Invacare stationary concentrator line. This 5-liter concentrator is small, quiet and lightweight and comes standard with the Invacare® SensO2® Oxygen Sensor. The Perfecto2 V unit incorporates many of the best features of the market-leading Invacare® Perfecto2™ Concentrator, including its contemporary, patient preferred external design and color.

Features

Pressure-based system is superior to timing-based systems

Self diagnostic electronics minimize troubleshooting time

Top handle for ease of mobility

Battery-free power loss alarm, Invacare® Sieve-GARD™ Monitor protects sieve from degradation, compressor 35 psi pressure-relief valve and low flow alarm

Provider Benefits

Robust design comes standard with Invacare® SensO2® oxygen monitor to simplify preventative maintenance schedules and lower costs

All Perfecto2 V stationary concentrators include a HomeFill system port for inventory flexibility

Patient-accessible reset button helps minimize emergency service calls

Patient Benefits

User friendly design with easy to see control panel, humidifier bottle holder and filter access

Low noise level and neutral color help to blend into any home environment Reliable concentrator provides unlimited, worry-free oxygen supply

HCPCS Code: E1390





- 1. Invacare® HomeFill® Oxygen System connection
- 2. HomeFill compressor and Ready Rack have been updated to coordinate with the Perfecto₂ Concentrator. Use with Invacare cylinders
- 3. Easy to maintain filter (not pictured)



Invacare Corporation

www.invacare.com

USA

One Invacare Way Elyria, Ohio 44035-4190 (800) 333-6900

Canada

570 Matheson Blvd. E., Unit 8 Mississauga, Ontario L4Z 4G4 Canada (800) 668 - 5324

©2013 Invacare Corporation. All rights reserved. Trademarks are identified by the symbols ™ and ®. All trademarks are owned by or licensed to Invacare Corporation unless otherwise noted. Specifications are subject to change without notification.

Form No. 09-064 Rev. 04/13 130375

















Model #	Dimensions	Weight	Shipping Weight	Quantity	Oxygen Flow	Flow Range	Maximum Outlet Pressure	Pressure Relief Mechanism
IRC5PO2V	23" H 13" W 11.5" D	39 lb.	45 lb.	1 Per Case 27 Per Pallet	5 LPM	0.5-5 LPM	5+/- 0.5 PSI	35 PSI +/- 3.5 PSI







Electrical















Filter Cabinet At All Flow Outlet HEPA Rates

Requirements 120 VAC Compressor Inlet +/- 10%, 60 Hz

Rated Current Input 3.0 A

Consumption 325 W @ 3 LPM

Average Power Sound Level 43 db.

8,000 ft. 6,000 ft. w/

Altitude Limited Warranty 3 Years HomeFill System

